

Lindner Raised Floor Technical Specs

LINDNER Products:

Nortec: Nortec is a floor system for the highest demands of fire and noise protection. Its excellent properties and high walking comfort make Nortec the standard system for office areas. Nortec panels have been classed by the Institut für Baubiologie (Institute for Building Biology) in Rosenheim, Germany, as hazard-free. They are made from regenerative raw materials and are emission-free.

Nortec Comfort: Nortec comfort floor system combines all the advantages of a raised floor system and a underfloor heating. This solution offers great freedom to planners and architects as there are no radiators. If the room gets too warm, Nortec comfort can also be used for cooling the room. As there is no drying time for the floor system Nortec comfort, it is immediately ready for use after the installation.

Ligna – Wooden Panel: Ligna is the classic access floor system for low-cost solutions in the office area. Allocated to the lowest emission class (E1), with minimum tolerances and fire resistance class F30, Ligna is an economical solution in commercially used rooms.

Lumen – Raised Glass Floor: Lumen means light!

With this floor system, you create a very special atmosphere. Lumen lets you see things that otherwise stay hidden. Transparent, translucent or coloured panels - you have a free hand in designing your floor.

Prodata – Aluminium Panel: Prodata double floor system is the ideal choice for clean rooms in the semiconductor industry. Extreme tolerances, top conductance and low weight are its main characteristics. Solid panels can be made into ventilation panels with almost any size free cross-sections (up to 42%) by drilling holes in them.

Ventec – Steel Ventilation Panel: Ventec steel ventilation panels are ideal for use in computer centres that require high rates of air flow and low withdrawal resistance.